



**ZINC OXIDE
GRADE 210HSA**

Description & Uses

Grade 210HSA is an extremely small particle French Process, statistically controlled zinc oxide produced from zinc metal. This grade has a higher surface area and reactivity and is used by the transparent rubber, latex, and plastic industries and in those applications where high reactivity is required. Grade 210HSA is available with surface treatment (210HSA-S).

Typical Technical Values*

Chemical Analysis (%)	Range	Nominal	Method
Zinc (as Zn or ZnO)	≥ 99.5	99.7%	USZ
Pb (Lead)	≤ 0.15%	0.1%	D4075
Cd (Cadmium)	≤ 0.025%	0.004%	D4075
Cu (Copper)	≤ 0.006%	nil	D4075
Fe (Iron)	≤ 0.006%	nil	D4075

Physical Properties

Surface Area (m ² /g)	8.0 – 10	9.0	D4315
Fineness Passing 325 mesh (%)	≥ 99.9%	99.98%	D4315
Heat Loss/Moisture (%)	< 0.3%	0.2%	D280
Specific Gravity	N/A	5.6	USZ
Apparent Density (Powder)	20-40	30	USZ

Standard packaging in 50 pound net weight bags on 48x40 wood pallets. 2,000 pounds net weight.

**U.S. Zinc can produce zinc oxide to meet individual customer specifications superceding the above. Please contact Customer Service for additional information.*

Revised 05/12/2014

U. S. ZINC

2727 Allen Parkway, Suite 800 Houston TX 77019 USA.

Phone (001) 713-926-1705, Fax (001) 713-924-4828

Info@USZinc.com WWW.USZinc.com