



Product Data Sheet

Product Type :	Zinc Dust XL - Premium (ASTM D520 Type III)			
Description :	Distilled fine metal powders. Optimally sized by screening and air classification.			
Specification :		USZ # 1 XLP	USZ # 5 XLP Superfine	USZ # 7 XLP Superfine
Total Zinc	% min.	99.0	98.5	98.5
Metallic Zinc	% min.	96	95	95
Lead	% max.	0.002	0.002	0.002
Cadmium	% max.	0.001	0.001	0.001
Iron	% max.	0.002	0.002	0.002
Average Particle Size	microns	5 – 8	3.5 - 5.5	2.5 - 4.5
Sieve +100 mesh (150 μ)	% max.	Trace	Trace	Trace
+200 mesh (75 μ)	% max.	0.1	0.01	0.01
+325 mesh (44 μ)	% max.	4	0.1	0.05
Specific Gravity		7.1	7.1	7.1
Typical Applications :	Chemicals Paints	Coatings Plating	Lubricants Purification	
Packaging :	Standard - up to 100 # in pails, up to 500 # in fiber drums, above 1,000 # in super sacks. Custom packaging upon request.			
Storage & Shelf Life :	Zinc dust is sensitive to moisture - store in a cool, dry location. Unsealing the container or storing in humid area will reduce the shelf life.			
Alternative Grades:	Additives, custom blends and tailoring for special requirements are available upon request.			
U.S. ZINC Products :	Zinc dust ; Zinc fines ; Zinc metal ; Zinc oxide.			
The information contained herein has been compiled to the best of US Zinc's knowledge, but is presented without any obligation. US Zinc assumes no liability for infringement of any patent which may result from the use of this information or products.				

Office : 2727 Allen Parkway
Suite 800
Houston, Texas 77011.

Tel: (713) 926-1705
Fax: (713) 924-4824
email: dustinfo@uszinc.com
web site: www.uszinc.com

(PDS-USZ- XL PREM)

Review date 02/18/2015 by BLD

Revision 7